



Product Information Sheet



Sheet Number: **0042**

Rev 22-11-06

GRAFFITSHIELD 2PAC Anti-Graffiti Paint & Clear Sealer

Graffitishield X 2 pac is an acrylic solvent based sealer with hardener for protecting surfaces against graffiti paints. Graffitishield X 2 pac is very durable and is a non-sacrificial coating that is highly chemical resistant making the removal of graffiti easier.

General Application Guide:

If using Coloured Graffitishield 2 Pac:

- Clean surface to be coated. If surface is a wall we suggest water blasting.
- Mix 2 parts of Graffitishield X 2 pac together. (8 hr pot life before it will harden)
- After mixing, apply 1 coat of coloured Concreshield X 2 pac by nap roller or airless spray.
- Allow to dry for 24 hrs with good ventilation.
- Apply 2nd coat of Concreshield X 2 pac.

If using as a Graffitishield 2Pac as a clear sealer:

- Clean surface and repaint wall to cover graffiti. We suggest using Shiledcoat Textureshield acrylic paint.
- Allow the 2 coats of Textureshield paint to dry and cure.
- Mix 2 parts of coloured Graffitishield X 2 pac together. (8 hr pot life before it will harden)
- After mixing, apply 1 coat of coloured Graffitishield X 2 pac by nap roller or airless spray.
- Allow to dry for 24 hrs with good ventilation.
- Apply 2nd coat of coloured Graffitishield X 2 pac.

To remove graffiti, we suggest either Graffitifree W (water based) or Graffitifree S (solvent based).

Graffitishield 2 pac can be applied by airless spray using a 517 tip or by brush or nap roller. Clean up immediately using a solvent thinner such as Xylene or R100 or general purpose thinners.

Notes: Graffitishield X 2 pac should not be applied late in the day or when moisture is present in the air or on the surface.

Specifications:

(all dry times are considered at 25° C and at 50% humidity)

Concreshield X 2 pac:

Surface Dry: 2-4 hours

Top Coat: 24 hours

Hard Dry: 3 -5 days

Wet Film Thickness: Approx. 120 microns

Dry Film Thickness: Approx. 40 microns

Thinning: No thinning required normally. If desired thin with General purpose thinners, or Xylene thinners sparingly.

Clean Up: Clean up turpentine or thinners immediately.



Picture: Graffitishield 2 Pac clear sealer applied to a factory sign. Graffiti is easy to remove using Graffitifree S (solvent)

Graffiti shield 2 Pac products come in 20 litre pails.

See MSDS for safety information

Features:

Easy to use

Reasonably Chemical Resistant

Flexible

Rolled or sprayed

Durable

Pre Mixed

Resists marking from chemical cleaners

Benefits:

Quick

Removal of graffiti easy

Allows for some substrate move-

Any painter can apply

Lasts for years

Small amount of mixing required

Touch up possible

Notes: There are many substrates on the market. Please consult Shieldcoat for further information regarding applications not on this sheet.