



# Product Information Sheet



Sheet Number: **0009**

Rev 30-07-07

## Features:

- Very Fine Texture
- Tintable
- Flexible
- Easy To Apply
- Low Build Finish
- Pre Mixed
- Thermotex Heat Reflective Version

## Benefits:

- Great Ambience
- Not Necessary To Paint After
- Allows for substrate movement
- Brush, nap roller or texture roller
- 1 or 2 coats
- Less labour. No mixing
- Reduces Temp.



## Provencal Sand Pre Mixed Acrylic Texture

### Provencal Sand

Provencal Sand is an acrylic texture paint suitable for most substrates to give a fine texture finish. It can be tinted to your choice of colour, cross brushed, rolled with a nap roller and is suitable for interiors and exteriors. It is premixed and is sold in a 15 litre pail. Provencal Sand is fine sand finish and is available in a heat reflective version called **Thermotex—Provencal Sand** which reduces temperatures in wall cavities and can even aid in increasing the substrates "R" value.

### General Application Guide:

After preparation apply 1 coat of Provencal Sand with a brush or roller choice.

### Substrate Application Information:

#### Fibre Cement:

- Apply Naturapatch Coarse & Naturatape to joins
- Fit Naturatrim plastic angles to corners
- Apply 1 coat of Alfresco Medium Sand by trowel
- Apply 1 coat of Provencal Sand by Nap or Texture Roller

#### Brick or Block:

- Fit Naturatrim plastic angles to corners
- Mix and apply Naturatex Daudeat High Build by trowel
- Apply 1 coat of Alfresco Medium Sand
- Apply 1 coat of Provencal Sand by Nap or Texture Roller

#### AAC panels:

- Fit Naturatrim plastic angles to corners
- Apply Naturapatch Coarse & Naturatape to joins
- Apply 1 coat of Alfresco Medium Sand
- Apply 1 coat of Provencal Sand by Nap or Texture Roller

#### Polystyrene panels:

- Fit Naturatrim plastic angles to corners
- Embed Naturamatt to entire surface as an impact coat
- Apply Naturatex Daudeat High Build by trowel
- Apply 1 coat of Alfresco Medium Sand
- Apply 1 coat of Provencal Sand by Nap or Texture Roller

**Note:** with polystyrene substrates that have a factory impact coat, apply Naturatape and Naturapatch to all joins. No need to apply Naturatex Daudeat High Build in this case.



### Specifications:

(all dry times are considered at 25° C and at 50% humidity)

**Surface Dry:** 4 -5 hours

**Top Coat:** 24 hours

**Hard Dry:** 4 -5 days

**Wet Film Thickness:** Approx. 240 microns

**Dry Film Thickness:** Approx. 120 microns

**Thinning:** No thinning required normally. If desired thin with water sparingly.

**Clean Up:** Clean up with water



Top Picture: Provencal Sand nap rolled .

Bottom Picture: Provencal Sand Texture Rolled.

Provencal Sand comes in 15 litre pails.

**Notes:** There are many substrates on the market. Please consult Shieldcoat for further information regarding applications not on this sheet.