



# Product Information Sheet



Sheet Number: **0101**

Rev 22-11-06

## ROOFBOND Ridgerite Bedding Compound Acrylic modified bedding compound for roof tiles and ridges caps

### Roofbond Ridgerite Bedding

Roofbond Ridgerite Bedding is an acrylic modified cement compound designed to bed ridge caps on concrete and terracotta roof tiles.

#### General Application Guide:

Mix one 20 kg bag with approximately 3 litres of water and 500mls of Shieldcoat Concrebond acrylic additive with an electric drill and paddle or by hand with a shovel. Place a suitable amount of compound along both sides of tile apex and bed down the ridge caps. Trowel excess of both sides.

#### Substrate Application Information:

- Clean surfaces thoroughly.
- Mix as above.
- Place a bedding guide across apex of roof.
- Apply a "sausage" of mixed Ridgerite bedding compound near guide on both sides of the apex to a height of approximately 50mm.
- Press ridge caps onto mix.
- Using a trowel, clean off excess bedding from side of ridge caps and tiles.
- Push weep holes randomly and spaced into bedding using a weep hole tool.
- Allow at least 2 hrs to dry or preferably overnight.
- Apply Roofbond Flexible Pointing as per pointing instructions.

#### NOTES:

Clean up: Clean tools with water.

Never apply if rain is likely within two hours.

Caution: Do not use when temperature is below 5°C.

#### Specifications:

(all dry times are considered at 25° C and at 50% humidity)

**Clean Up:**Clean up with water



Top Picture: Placing a Bedding Guide on apex of roof.

Middle Picture: Roofbond Ridgerite Bedding Compound with ridge caps placed.

Bottom Picture: Roofbond Flexible Pointing.

Roofbond Ridgerite Bedding Compound comes in 20 kg bags.

**See MSDS for safety information**

### Features:

Excellent Adhesion



Simple to Mix



Good "Stand Up"



Easy To Apply



Durable



Pre Mixed



Approved when used in conjunction with Roofbond Flexible Pointing



### Benefits:

Good mechanical fastening of ridges



Electric or by Hand



Supports Ridge Tile with minimal sag



Trowel glides over compound



Warranted System for 10 years



In 20 kg bag means no guess work on mixes



C3 rated system approved.



**Notes:** There are many substrates on the market. Please consult Shieldcoat for further information regarding applications not on this sheet.