



# Product Information Sheet



Sheet Number: **0062**

Rev 8- 4 -2010



## ROOFBOND Shieldseal W PLUS

**Shieldseal W PLUS:** is an acrylic sealer designed to penetrate and prime fibro and metal roofs (either factory painted or plain zinc), in preparation for Roofbond roof coatings to follow. Shieldseal W PLUS is airless sprayed using a 517 tip and dries clear.

### General Application Guide:

Zincalume and Colourbond metal roofs:

- Water blast roof with at least 3000 p.s.i.
- Apply one coat of Shieldseal W+ with 517 airless tip
- Apply 2 coats of Roofbond roof paint with 521 airless tip.

Fibro Roof:

- Apply one coat of Shieldseal W+ with 517 airless tip
- Apply 1 or 2 coats of fillabond with 521 airless tip (optional)
- Apply 2 coats of Roofbond roof paint with 521 airless tip.



### specifications:

(dry times are considered at 25°)

#### Roofbond Shieldseal W PLUS :

**Surface Dry:** 1/2-2 hours

**Top Coat:** 2-4 hours

**Hard Dry:** 3 -5 days

**Wet Film Thickness:** N/A

**Dry Film Thickness:** N/A

**Thinning:** No thinning required normally. If desired thin with water sparingly.

**Clean Up:** Clean up with water



Top Picture:

Shieldseal W PLUS being sprayed over a factory painted metal roof

Left Picture:

Shieldseal W PLUS available in 15 litre pail.

### Features:

- Penetrating Primer
- Clear
- Flexible
- Easy To Apply
- Promotes Paint Adherence
- Pre Mixed
- Excellent adhesion properties

### Benefits:

- Good Adhesion
- Dries clear
- Allows for some substrate move-
- Airless Sprayed
- Job flows with ease
- Water based
- Environmentally friendly

**Notes:** There are many substrates on the market. Please consult Shieldcoat for further information regarding applications not on this sheet.

See MSDS for safety information

Shieldcoat has become one of the first paint manufacturer in Australia to meet the international environmental standard, ISO 14001