



Product Information Sheet



Sheet Number: **0033**

Rev 18-05-2010

Concrete Slab Repair

Acrylic water based Driveway Concrete Repair

Concrete Slab Repair is an acrylic crack repair coating designed to fill reasonable sized surface cracking in existing concrete and other driveway surfaces and to remain flexible enough for some substrate movement. Slab Repair is premixed in a concrete natural colour and is applied by spatula or trowel.

General Application Guide: Cracks should be ground out with an angle grinder to a depth of 5-10 mm first. Apply slab repair with a spatula into prepared cracks, feather compound out so crack repair is smooth to surface using foam rubber. Cement slurry (made up of only 20 ml cement to 500ml slab repair) is permitted to be added to Slab Repair to improve drying and strength on larger fills. When totally dry, Stencilshield, Concreshield x or Floorshield Concrete coatings can then be applied.



Slab Repair:

Surface Dry: 4 -5 hours

Top Coat: 24hr or when totally dry

Hard Dry: 3 -5days

Wet Film Thickness: N/A

Dry Film Thickness: N/A

Thinning: No thinning required normally. If desired thin with water sparingly.

Clean Up: Clean up with water



Notes:

Cement Slurry: Do not mix entire pail as it sets quite quickly. We recommend mixing a small amount and using immediately.



Picture Above : Slab Repair applied by Spatula

Picture Right: Slab Repair comes in various size pail

See MSDS for safety information

Features:

- Convenient Packaging
- Natural Concrete Colour
- Flexible
- Easy To Apply
- Not a messy 2 Pac system
- Pre Mixed
- Crack Bridges

Benefits:

- Various sizes to suit job size
- Close match to concrete
- Allows for some substrate move-
- Spatula Applied
- Water based
- Environmentally friendly
- Will not Delaminate near cracks

Shieldcoat has become one of the first paint manufacturer in Australia to meet the international environmental standard, ISO 14001