



Product Information Sheet



Sheet Number: **003 I**

Rev 20-05-2010


STENCILSHIELD/CONCRETE Primer Plus

Acrylic water based Concrete Primer

STENCILSHIELD /CONCRETE

Primer Plus is an acrylic primer designed to penetrate concrete in preparation for Stencilshield, and Floorshield coatings to follow. Primer Plus must be rolled with a nap roller and dries clear.

General Application Guide: Roll 1 coat of primer Plus with a nap roller only after cleaning and repair steps listed in the Stencilshield and Floorshield application sheets.



Specifications:

(dry times are considered at 25°)

Stencilshield /Floorshield Primer Plus:

Surface Dry: 1/2-2 hours

Top Coat: 2-4 hours

Hard Dry: 3 -5 days

Wet Film Thickness: N/A

Dry Film Thickness: N/A

Thinning: No thinning required normally. If desired thin with water sparingly.

Clean Up: Clean up with water



Picture Left: Primer Plus applied to prepared concrete.

Top Picture: Primer Plus dry and stencil pattern laid.

Primer Plus comes in 15 litre pails.

See MSDS for safety information

Features:

- Penetrating Primer
- Clear Colour
- Flexible
- Easy To Apply
- Promotes Stencilshield Adherence
- Pre Mixed
- Crack Bridges

Benefits:

- Good Adhesion
- Dries clear
- Allows for some substrate move-
- Nap Roller Applied
- Water based
- Stirring only required
- Environmentally friendly

Notes:

There are many substrates on the market. Please consult Shieldcoat for further information regarding applications not on this sheet.

Shieldcoat has become one of the first paint manufacturer in Australia to meet the international environmental standard, ISO 14001