



Product Information Sheet



Sheet Number: **0072**

Rev 22-11-06

TERRABOND

Acrylic water based non-glazed terracotta clear coating

Terrabond

is an acrylic coating designed to seal and produce a clear gloss to non-factory glazed terracotta tile roofs. It is applied by airless spray using a 517-521 tip size.

General Application Guide:

Apply one coat of Shieldseal W sealer and 2 coats of Terrabond using an airless spray gun.

Substrate Application Information:

Non-Glazed Terracotta Tile Only:

- Water blast roof with at least 3000 p.s.i.
- Apply one coat of Shieldseal W with 517 airless tip
- Apply 2 coats of Terrabond with 517-521 airless tip



Specifications:

(all dry times are considered at 25° C and at 50% humidity)

Roofbond Shieldseal W:

Surface Dry: 4 -5 hours

Top Coat: 12 hours

Hard Dry: 4 -5 days

Wet Film Thickness: Approx. 180 microns

Dry Film Thickness: Approx. 90

Top Picture: Shieldseal W Plus come in 15 litre pails.

See MSDS for safety information

Features:

Good Adhesion



Dries Clear



Flexible



Easy To Apply



Durable



Pre Mixed



Not Recommended over glazed tiles



Benefits:

Prepares Substrate



Covers over well



Allows for some substrate move-



Airless Sprayed



Part of a warranty for 10 years



Stirring only required



Can be recoated



Notes: There are many substrates on the market. Please consult Shieldcoast for further information regarding applications not on this sheet.