



Product Information Sheet



Sheet Number: **0012**

Rev 22-11-06

TEXTURESHIELD Render Paint Acrylic water based render paint

Textureshield is an acrylic render paint designed to coat or recoat all rendered surfaces. Textureshield comes in a range of colours and is applied by nap roller or airless spray using a 521 tip size. This product is warranted for 10 years against peeling or cracking. Great for Tilt Slab buildings. Available in **Textureshield Thermo** a heat reflective version capable of improving the substrate's R value. **Textureshield Thermo** will provide the equivalent to R22 (imperial) in most cases. **Textureshield Thermo** works well on Tilt Slab buildings to reduce heat ingress into office space. It can be used in conjunction with **Thermobond HRC** on the roof to reduce heat from that source as well.



General Application Guide:

Apply one coat of Sealer and 2 coats of Textureshield paint using an airless spray with a 521 tip or nap roller.

Substrate Application Information:

Tilt Slab with bondbreaker:

- Apply Mouldshield C cleaner diluted 5:1 with water
- Soft broom and hose or water blast.
- Apply 1 coat of Naturaprime with 517 airless tip or nap roller
- Apply 2 coats of Textureshield Paint with 521 airless tip or nap roller.

Other rendered surfaces:

- Water blast with at least 3000 p.s.i.
- Apply 1 coat of Naturaprime with 517 airless tip or nap roller
- Apply 2 coats of Textureshield Paint with 521 airless tip or nap roller.

Specifications:

(all dry times are considered at 25° C and at 50% humidity)

Textureshield:

Surface Dry: 4 -5 hours

Top Coat: 12 hours

Hard Dry: 4 -5 days

Wet Film Thickness: Approx. 180 microns

Dry Film Thickness: Approx. 90 microns

Thinning: No thinning required



Top Picture: Textureshield on a rendered home.

Bottom Picture: Textureshield on a Tilt Slab wall.

Textureshield comes in 15 litre pails.

See MSDS for safety information

Features:

Low Gloss to Full Gloss



Choice of Colours



Flexible



Easy To Apply



Durable



Pre Mixed



Available in Thermobond Heat Reflective Version



Benefits:

Low Dirt Pick Up
Easy To Clean



Suits all Decors



Allows for some substrate move-



Airless Sprayed or
Nap Rolled



Warranted for 10
years



Stirring only re-
quired



Thermobond Re-
duces cavity temp-



Notes: There are many substrates on the market. Please consult Shieldcoast for further information regarding applications not on this sheet.